

Model List

- HD 320B | Wall Mounted Music Speaker

Product Introduction

Introducing the HD 320B, a compact powerhouse designed to solve one of the biggest challenges in modern audio installation: delivering rich, high-quality sound in spaces where room is at a premium. This 3.5-inch wall-mounted music speaker combines a remarkably slim, unobtrusive profile with surprisingly robust audio performance. Its sleek, minimalist ABS housing in a professional black finish allows it to blend seamlessly into any environment, from corporate boardrooms to chic retail boutiques. At the heart of the HD 320B is a carefully engineered coaxial driver, which provides point-source accuracy and exceptionally wide, even sound dispersion. This ensures that every listener in the room enjoys a clear and consistent audio experience, free from the “hot spots” and “dead zones” common with other compact speakers. For architects, designers, and installers who require a discreet, space-efficient, and sonically impressive solution, the HD 320B is the definitive choice for background music, paging, and presentations.



HD 320B

Key Features

- Compact 3.5-inch wall-mounted music speaker for spaces where room is at a premium.
- Remarkably slim, unobtrusive profile with robust audio performance.
- Sleek, minimalist ABS housing in a professional black finish for seamless integration.
- Carefully engineered coaxial driver provides point-source accuracy and wide sound dispersion.
- Delivers 20W RMS rated input and 40W peak power handling.
- Supports 100V (20W, 10W) and 70V (10W, 5W) power taps, with 16Ω impedance.
- Frequency response of 120Hz - 20kHz and sensitivity of 85dB (±2dB).
- Maximum peak SPL of 99dB (±2dB) with a 120 x 120 coverage angle.
- Complies with EN IEC 62368-1 safety standard.
- Ideal for background music, paging, and presentations in corporate boardrooms and retail boutiques.

Technical Specification

HD 320B	
Rated Input (RMS)	20W
Peak Power Handling	40W (Calculated)
Power Taps (100V)	20W, 10W
Power Taps (70V)	10W, 5W
Impedance	16Ω
Frequency Response	120Hz - 20kHz
Frequency Range (-10 dB)	120Hz - 20kHz
Sensitivity (1W/1m)	85dB (±2dB)
Maximum Peak SPL	99dB (±2dB)
Coverage Angle	120 x 120
Speaker Component	3.5" coaxial
Safety	EN IEC 62368-1
Dust & Water Protection	NA
Material & Finish	Housing: ABS. Available in Black.
Mounting	Wall Mount
Connectors	Spring Clip Terminals
Dimensions (W x H x D)	148 x 138 x 27 mm
Weight	1.23 kg

For further specifications or application details, please contact us. Specifications may change without prior notice. Technical modifications reserved.