

Model List

- PS 801 | Conference System microphone Charger

Product Introduction

The PS 801 is a robust 28-port USB charger designed to simultaneously charge up to 28 devices. It features multiple short-circuit protections that automatically cut off the output in case of a short circuit, as well as input and output overcurrent and undervoltage protection. The charger intelligently identifies connected devices to provide a maximum output current of 1A. Additionally, it includes leakage protection that automatically cuts off output in case of leakage. The PS 801 is equipped with a power switch with a status indicator light and a digital display for real-time visualization of charging voltage, ensuring clear and safe operation.



PS 801

Key Features

- Robust 28-port USB charger designed for simultaneous charging of up to 28 devices.
- Intelligent device identification provides a maximum output current of 1A per port.
- Comprehensive protection includes short-circuit, overcurrent, undervoltage, and leakage automatic cut-off.
- Digital display for real-time visualization of charging voltage ensures safe operation.
- Power switch equipped with status indicator light for clear operational status.
- Total power output of 90W with a stable 5V 1A per channel.
- Compact desktop design with dimensions of 420 x 180 x 61 mm.
- Advanced safety features automatically cut off output in case of electrical faults.

Technical Specification

PS 801	
Output	5V 1A
Power	90W
Dimensions (W x D x H)	420 x 180 x 61 mm
Weight	3.3 kg